

4-WEGS CASSETTE CC



BINNENUNITS				
Unit	ACP-09CC25AERI/I+	ACP-12CC35AERI/I+	ACP-18CC50AERI/I+	
Rooster	ACP-09CC25AERI/P	ACP-12CC35AERI/P	ACP-18CC50AERI/P	

TECHNISCHE SPECIFICATIES

Capaciteit (W)	2638	3520	5280
Capaciteit (W)	2931	3810	6568
Debiet (m ³ / h) H / M / L	580 / 500 / 450	620 / 520 / 330	660 / 540 / 300
Ontvochtigingscap. (L / h)	1.0	1.2	1.8
Geluidsdruk (dBA) H / M / L	38 / 33 / 29 / 25.5	42 / 38.5 / 31.5 / 25.5	44 / 41 / 31.5 / 25
Geluidsvermogen (dB)	53	55	59
Opvoerhoogte pomp (mm)	750	750	750
Dia. cond. leiding (mm)	25	25	25
Afm. Verpakking (mm)	715 x 295 x 640	715 x 295 x 640	715 x 295 x 640
Afm. Unit (mm) L x H x Br	570 x 245 x 570	570 x 245 x 570	570 x 245 x 570
Afm. Verp. rooster (mm)	715 x 115 x 700	715 x 115 x 700	715 x 115 x 700
Afm. rooster (mm) L x H x Br	620 x 50 x 620	620 x 50 x 620	620 x 50 x 620
Gewicht Bruto / Netto (kg)	16.8 / 14.5	18.8 / 16.1	19 / 16.2
Gewicht rooster Br / Net (kg)	4.3 / 2.7	4.3 / 2.7	4.3 / 2.7
Dia. leiding (vloeibaar)	1 / 4"	1 / 4"	1 / 4"
Dia. leiding (gas)	3 / 8"	3 / 8"	1 / 2"
Verbindingskabel (mm ²)	5G1,5	5G1,5	5G1,5