

SPLIT R32



HYDROBOX

UNITS	HPS-42HM65AERI/11H3s	HPS-84HM100AERI/11H3s	HPS-120HM155AERI/11H9s
-------	----------------------	-----------------------	------------------------

TECHNISCHE SPECIFICATIES

UNIT	Comptibele buitenunits (kW)		6	8 / 10	12 / 14 / 16
	Drempel watertemperatuur (°C)	Koelen	5 - 30	5 - 30	5 - 30
		Verwarmen	12 - 65	12 - 65	12 - 65
		Warm water (sanit.)	10 - 60	10 - 60	10 - 60
	Afmetingen verpakking (mm)		520 x 1050 x 360	520 x 1050 x 360	520 x 1050 x 360
	Afmetingen unit (mm) L x H x P		420 x 790 x 270	420 x 790 x 270	420 x 790 x 270
	Gewicht bruto / netto (kg)		47 / 41	47 / 41	49 / 43
	Elektr. verwarming	Verm. (kW)	3	3	9
Niveau(s)		1	1	3	
HYDRO	Diameter aansluiting (")		R1	R1	R1
	Manometrische hoogte pomp (m)		9	9	9
	Druk veiligheidsventiel (bar)		3	3	3
	Drempel flowswitch (m3/h)		<0.36	<0.36	<0.60
ELEKTRISCH	Voeding (V)		220-240Vac 1Ph, 50Hz	220-240Vac 1Ph, 50Hz	380-415Vac 3Ph+N, 50Hz
	Zekering (A)		20	20	16
	Voedingskabel (mm2)		3G2,5	3G2,5	5G2,5
	Aansluiten via		Binnenunit	Binnenunit	Binnenunit
	Kabel bedieningspaneel		4draads	4draads	4draads